



- GENERAL NOTES**
1. CONTRACTOR TO COORDINATE WITH CITY OF HANOVER AND UTILITY CONTRACTOR IN THE PUBLIC RIGHT OF WAY.
 2. CONTRACTOR TO COORDINATE BUILDING, GAS, ELECTRIC, COMMUNICATIONS UTILITY MARKERS LOCATED WITH ARCHITECT'S UTILITY MARKERS.
 3. CONTRACTOR TO COORDINATE AND VERIFY SITE LOCATING PLAN WITH ARCHITECT'S MARKERS AND/OR PERMITS.
 4. ALL UTILITY MARKERS SHALL BE PRE-CAST 48" HIGH, WITH IDENTIFYING COLORED POLYURETHANE PAINT.
 5. CONTRACTOR SHALL VERIFY ALL UTILITY MARKERS WITH WATER LATERAL CROSSER BEFORE PROVIDING INSULATION. REPAIRING WATER MAIN AND LATERAL MARKER CROSSING WHERE THE VERTICAL SEPARATION IS LESS THAN 10" TO INSURE PROPER MARKER CONTACT WITH OWNERS' DESIGN APPROVED UTILITY MARKERS LOCATING WITH OWNERS' DESIGN APPROVED CONTRACTOR TO PROVIDE 2" INSULATION BETWEEN WATER MAIN AND OTHER SEWER AT ALL INTERSECTIONS.

- WATERMAIN NOTES**
1. ALL WATERMAIN AND WATER SERVICES 12" AND LARGER SHALL BE EXCISE IRON, CLASS 50 AND WRAPPED IN POLYETHYLENE WRAP.
 2. ALL WATERMAIN SHALL BE 15' MINIMUM COVER UNLESS OTHERWISE SPECIFIED AND APPROVED BY THE CITY OF HANOVER.
 3. ALL WATERMAIN MARKERS SHALL BE POLYURETHANE GRANITE'S COLORED AND APPROVED BY THE CITY OF HANOVER.
 4. WATERMAIN AND ASSOCIATED STRUCTURES ARE TO CONFORM TO THE CITY OF HANOVER'S SPECIFICATIONS AND TO THE CONSTRUCTION IN RESOLUTION.
 5. ALL WATERMAIN SHALL BE 15' MINIMUM COVER UNLESS OTHERWISE SPECIFIED AND APPROVED BY THE CITY OF HANOVER.
 6. ALL JOINTS SHALL BE RESTRAINED WITH REINFORCEMENT.

- EXISTING SANITARY SEWER
- PROPOSED SANITARY SEWER
- EXISTING STORM SEWER
- PROPOSED STORM SEWER
- PROPOSED 6" BLUE GRITON UNDERGRATE
- EXISTING WATERMAIN
- PROPOSED 12" WATERMAIN
- DOUBLE LAYER BLUE GREEN LABELS
SEE DETAIL 4/SHEET C4.01